epd-global
Powered by EPD-Norway

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

Double Walled Cable Protection Pipes in coil

PIPELIFE

EPD-Global

Owner of the declaration:
Pipelife Sverige AB

Product:
Double Walled Cable Protection Pipes in coil

Declared unit:
1 kg

This declaration is based on Product Category Rules:
CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR Part A: Construction products and services. Ver. 2.0 March 2021

Program operator:
EPD-Global

Declaration number:
NEPD-4454-3718

Issue date:
10.05.2023

Latest revision
v1.0 Date: 27.05.2026

Valid to:
10.05.2028

EPD software:
LCAno EPD generator ID: 1589666

General information

Product

Double Walled Cable Protection Pipes in coil

Owner of the declaration:

Pipelife Sverige AB
Contact person:
Phone: +46 513 22114
e-mail: yvette.lennartsson@pipelife.com

Program operator:

EPD-Global
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-global.com

Manufacturer:

Pipelife Sverige AB

Declaration number:

NEPD-4454-3718

Place of production:

Pipelife Sverige AB
Box 50
SE-524 02 Ljung , Sweden

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR Part A: Construction products and services. Ver. 2.0 March 2021

Management system:

EN ISO 9001:2015 and EN ISO 14001:2015

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Organisation no:

SE556087042901

Declared unit:

1 kg Double Walled Cable Protection Pipes in coil

Issue date:

10.05.2023

Declared unit with option:

A1, A2, A3, A4, A5, C1, C2, C3, C4, D

Valid to:

10.05.2028

Year of study:

2025

Functional unit:

Not relevant

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global.

Developer of EPD: Yvette Lennartsson

Reviewer of company-specific input data and EPD: Bjørn Svensson

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools. Approval number: NEPDT49.

Approved:

Third party verifier:

Vito D'Incognito, Take Care International, Take Care International

(no signature required)

Product

Product description:

Double walled cable protection pipes in coil.
Class SRN according to Verksnorm 5200.

Product specification

Product related data to be found at Pipelife Sverige AB product catalogue https://catalog.pipelife.com/se or Danish product catalogue https://catalog.pipelife.com/dk

Materials	kg	%
Pigments	0.006	0.60
Polyethylene (HDPE)	0.6299	62.99
Polyethylene (HDPE) recycled	0.3642	36.42
Total	1.00	100.00

Technical data:

PE material with density 960 kg/m3.
Produced according Verksnorm 5200.

Market:

Europe, with scenario made for the Swedish and Danish market.

Reference service life, product

Lifetime on product calculated more than 100 years.

Reference service life, building or construction works

Not relevant

LCA: Calculation rules

Declared unit:

1 kg Double Walled Cable Protection Pipes in coil

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804:2012+A2:2019. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Pigments	ecoinvent 3.6	Database	2019
Polyethylene (HDPE)	ecoinvent 3.6	Database	2019
Polyethylene (HDPE) recycled	ecoinvent 3.6	Database	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X

System boundary:

EPD process A1 – D Double Walled Cable Protection pipes in coil



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

A5 = 5 % product losses during installation are estimated by the company. According to NPCR 028, other activities such as excavating/backfilling trenches and other additional materials are not included, these are expected to be included at construction level assessments.

C1 = According to NPCR 028, other activities such as excavating/backfilling trenches and other additional materials are not included, these are expected to be included at construction level assessments. This module can therefore be included with zero impact.
C3 - C4 =Waste treatment of the product follows the default values provided in EN 50693, Product Category Rules for life cycle assessments of electronic and electrical products and systems, table G.4. This table specified how different types of raw materials used in A1 will likely be treated during the end-of-life of the product. Waste treatments in C3 include material recycling and incineration with and without energy recovery and fly ash extraction. Disposal in C4 consist of landfilling of different waste fractions and of ashes.
D = The recyclability of metals and plastics allows the producers a credit for the net scrap that is produced at the end of a product's life. The benefits from recycling of net scrap are described in formula from EN 15804:2012+A2:2019. Substitution of heat and electricity generated by the incineration with energy recovery of plastics is also calculated in module D.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 6 (km)	53.3 %	100.00	0.023	l/tkm	2.30

Assembly (A5)	Unit	Value			
Product loss during installation (percentage of cable pipe)	Units	0.05			

Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 6 (km)	36.7 %	100.00	0.043	l/tkm	4.30

Waste processing (C3)	Unit	Value			
Waste treatment of plastic mixture, incineration with energy recovery and fly ash extraction (kg)	kg	0.003			
Waste treatment of polyethylene (PE), incineration with energy recovery and fly ash extraction (kg)	kg	0.497			
Landfilling of ashes from incineration of Polyethylene (PE), process per kg ashes and residues (kg)	kg	0.1821			

Disposal (C4)	Unit	Value			
Landfilling of plastic mixture (kg)	kg	0.3179			
Landfilling of ashes from incineration of Plastic mixture, process per kg ashes and residues (kg)	kg	0.0001049			
Landfilling of ashes from incineration of Polyethylene (PE), process per kg ashes and residues (kg)	kg	0.01751			

Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of electricity (MJ)	MJ	0.9684			
Substitution of thermal energy, district heating (MJ)	MJ	14.65			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact												
	Indicator	**Unit**	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	GWP-total	kg CO_2 -eq	1.49E+00	1.42E-01	4.01E-02	8.72E-03	1.63E-01	0	1.63E-02	1.52E+00	3.73E-02	-8.80E-02
	GWP-fossil	kg CO_2 -eq	1.49E+00	1.42E-01	3.97E-02	8.71E-03	1.62E-01	0	1.63E-02	1.52E+00	3.73E-02	-8.49E-02
	GWP-biogenic	kg CO_2 -eq	7.44E-03	5.81E-05	4.48E-04	3.73E-06	3.99E-04	0	6.76E-06	1.76E-05	3.75E-06	-1.75E-04
	GWP-luluc	kg CO_2 -eq	5.31E-04	4.98E-05	4.77E-05	2.65E-06	3.21E-05	0	5.81E-06	3.33E-06	8.55E-07	-2.93E-03
	ODP	kg CFC11 -eq	4.56E-08	3.24E-08	2.22E-09	2.10E-09	4.47E-09	0	3.70E-09	2.21E-09	1.09E-09	-6.19E-03
	AP	mol H+ -eq	5.10E-03	5.74E-04	2.79E-04	2.80E-05	3.14E-04	0	4.69E-05	2.24E-04	2.80E-05	-7.00E-04
	EP-FreshWater	kg P -eq	2.74E-05	1.12E-06	5.36E-06	6.93E-08	1.72E-06	0	1.31E-07	2.54E-07	4.58E-08	-7.55E-06
	EP-Marine	kg N -eq	9.01E-04	1.69E-04	1.21E-04	6.14E-06	6.77E-05	0	9.29E-06	1.02E-04	4.76E-05	-2.29E-04
	EP-Terrestial	mol N -eq	1.00E-02	1.87E-03	9.42E-04	6.85E-05	7.10E-04	0	1.04E-04	1.11E-03	1.10E-04	-2.47E-03
	POCP	kg NMVOC -eq	4.61E-03	5.74E-04	2.67E-04	2.69E-05	2.91E-04	0	3.98E-05	2.69E-04	3.89E-05	-6.82E-04
	ADP-minerals&metals[1]	kg Sb-eq	1.42E-05	3.86E-06	6.96E-07	1.55E-07	9.76E-07	0	4.51E-07	1.08E-07	2.93E-08	-8.45E-07
	ADP-fossil[1]	MJ	4.73E+01	2.15E+00	1.18E+01	1.41E-01	3.09E+00	0	2.47E-01	1.89E-01	8.17E-02	-1.21E+00
	WDP[1]	m^3	2.56E+02	2.05E+00	6.45E+00	1.08E-01	1.34E+01	0	2.39E-01	1.19E+00	7.08E-01	-1.51E+01

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

The products are produced on 100% renewable energy according mass balance principle.

Additional environmental impact indicators

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	PM	Disease incidence	4.38E-08	1.02E-08	7.17E-09	8.00E-10	3.23E-09	0	1.00E-09	1.17E-09	5.39E-10	-4.24E-08
	IRP[2]	kgBq U235 -eq	6.21E-02	9.38E-03	9.44E-01	6.18E-04	5.09E-02	0	1.08E-03	5.96E-04	3.94E-04	-7.76E-03
	ETP-fw[1]	CTUe	9.61E+00	1.58E+00	4.99E-01	1.03E-01	6.28E-01	0	1.83E-01	4.78E-01	1.04E-01	-6.61E+00
	HTP-c[1]	CTUh	4.90E-10	0.00E+00	6.40E-11	0.00E+00	3.00E-11	0	0.00E+00	4.20E-11	3.00E-12	-1.21E-10
	HTP-nc[1]	CTUh	1.05E-08	1.71E-09	1.62E-09	1.00E-10	7.91E-10	0	2.00E-10	1.59E-09	8.60E-11	-6.33E-09
	SQP[1]	dimensionless	2.43E+00	1.48E+00	1.56E-01	1.62E-01	2.48E-01	0	1.73E-01	2.58E-01	3.00E-01	-8.12E+00

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use												
Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	PERE	MJ	1.77E+00	3.03E-02	6.32E-02	1.78E-03	9.42E-02	0	3.54E-03	8.33E-03	3.89E-03	-7.50E+00
	PERM	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PERT	MJ	1.77E+00	3.03E-02	6.32E-02	1.78E-03	9.42E-02	0	3.54E-03	8.33E-03	3.89E-03	-7.50E+00
	PENRE	MJ	6.99E+00	2.15E+00	1.19E+01	1.41E-01	1.08E+00	0	2.47E-01	1.89E-01	8.17E-02	-1.21E+00
	PENRM	MJ	4.22E+01	0.00E+00	0.00E+00	0.00E+00	2.11E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	PENRT	MJ	4.92E+01	2.15E+00	1.19E+01	1.41E-01	3.20E+00	0	2.47E-01	1.89E-01	8.17E-02	-1.21E+00
	SM	kg	3.64E-01	0.00E+00	0.00E+00	0.00E+00	1.82E-02	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	6.57E-02	1.09E-03	3.87E-03	6.23E-05	3.56E-03	0	1.26E-04	2.16E-04	8.28E-05	-1.31E-03
	NRSF	MJ	1.00E-02	3.87E-03	3.85E-03	2.09E-04	1.94E-03	0	4.52E-04	1.85E-02	1.90E-03	-4.45E-01
	FW	m^3	1.93E-02	2.26E-04	6.33E-02	1.61E-05	4.17E-03	0	2.64E-05	3.68E-04	9.89E-05	-9.04E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

End of life - Waste

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	HWD	kg	7.24E-03	1.10E-04	8.19E-03	7.74E-06	9.22E-03	0	1.27E-05	1.54E-01	1.48E-02	-5.71E-05
	NHWD	kg	6.53E-02	1.03E-01	4.42E-02	1.23E-02	3.24E-02	0	1.20E-02	8.47E-02	3.26E-01	-2.87E-02
	RWD	kg	4.68E-05	1.46E-05	1.95E-04	9.66E-07	1.30E-05	0	1.68E-06	5.40E-07	5.34E-07	-6.36E-06

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

End of life - Output flow

Indicator		Unit	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
	CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	1.43E-06	0	0.00E+00	0.00E+00	2.85E-05	0.00E+00
	MER	kg	0.00E+00	0.00E+00	2.09E-02	0.00E+00	2.60E-02	0	0.00E+00	5.00E-01	6.97E-07	0.00E+00
	EEE	MJ	0.00E+00	0.00E+00	1.24E-02	0.00E+00	4.90E-02	0	0.00E+00	9.68E-01	4.52E-05	0.00E+00
	EET	MJ	0.00E+00	0.00E+00	1.88E-01	0.00E+00	7.42E-01	0	0.00E+00	1.47E+01	6.85E-04	0.00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0*10-3 = 0.009"

Biogenic Carbon Content

Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0.00E+00
Biogenic carbon content in accompanying packaging	kg C	0.00E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Not relevant

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products											
Indicator	**Unit**	A1	A2	A3	A4	A5	C1	C2	C3	C4	D
GWPIOBC	kg CO_2 -eq	1.42E+00	1.42E-01	3.97E-02	8.72E-03	1.59E-01	0	1.63E-02	1.52E+00	3.73E-02	-8.68E-02

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010. Environmental labels and declarations - Type III environmental declarations - Principles and procedures. International Organization for Standardization.
ISO 14044:2006. Environmental management - Life cycle assessment - Requirements and guidelines. International Organization for Standardization.
EN 15804:2012+A2:2019. Environmental product declaration - Core rules for the product category of construction products. European Committee for Standardization.
ISO 21930:2017. Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products. International Organization for Standardization.
EN 50693:2019. Product category rules for life cycle assessments of electronic and electrical products and systems. European Committee for Standardization.
Ecoinvent v3, 2019. Allocation, cut-off by classification. Swiss Centre of Life Cycle Inventories.
Iversen et al., (2021). eEPD v2021.09, background information for EPD generator tool system verification, LCA.no. Report number: 07.21. System verification report.
Philis et al., (2022). EPD generator for NPCR 028 part B for cable pipes, background information for EPD generator application and LCA data, LCA.no Report number: 06.22. PCR verification report.
EPD Norway (2022). NPCR Part A: Construction products and services. The Norwegian EPD foundation. Version 2.0 published 24.03.2021.
EPD Norway (2022). NPCR 027 Part B for cable pipes. The Norwegian EPD foundation. Version 2.0 published 31.03.2022.

epd-global Powered by EPD-Norway	**Program operator and publisher** EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: e-mail: web:	+47 977 22 020 post@epd-norge.no www.epd-global.com
PIPELIFE	**Owner of the declaration:** Pipelife Sverige AB Box 50 , SE-524 02 Ljung , Sweden	Phone: e-mail: web:	+46 513 22114 yvette.lennartsson@pipelife.com
LCA.no	**Author of the Life Cycle Assessment** LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: e-mail: web:	+47 916 50 916 post@lca.no www.lca.no
LCA.no	**Developer of EPD generator** LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: e-mail: web:	+47 916 50 916 post@lca.no www.lca.no
ECO PLATFORM EPD VERIFIED	ECO Platform ECO Portal	web: web:	www.eco-platform.org ECO Portal